

vinyl planks

care and maintenance instructions

BERRY  ALLOC

Version: 22/07/2020

1. PROTECTION

DOORMATS

To keep your floor in good condition, it is important to place non-rubber backed doormats at all entrances. Doing so prevents dirt or grit on your floor. These abrasive particles could damage the floor, causing scratches. Do not use rubber-backed mats, as long-lasting contact with rubber can cause permanent discolouration. Never place doormats on a wet floor.

SOFT WHEELS

Rolling office chairs, furniture legs, fitness appliances, etc. should be fitted with soft, non-rubber casters, to avoid permanent damage to your floor. Use a suitable desk mat.

FELT PADS

You should use felt pads or protective feet for items that contain rubber, such as chair legs, furniture legs, fitness appliances, etc.

2. CLEANING

INITIAL CLEANING

First, remove all dirt and dust from the flooring with a brush or vacuum cleaner. Then clean with water and a pH neutral appropriate cleaning agent, at least twice and until the water stays clean. We strongly recommend using the BerryAlloc Vinyl Planks cleaner. Any other cleaning product may contain agents that damage resilient floor surfaces. The coating of the top-layer renders a specific treatment after installation unnecessary.

REGULAR CLEANING INSTRUCTIONS

Vacuum or wet mop. When required, use a solution of clean water and a mild, pH-neutral detergent (BerryAlloc Vinyl Planks Cleaner). Do not flood the floor or leave a puddle of water on the floor. Rinse thoroughly and soak up residual water.

NB: if water is not removed carefully and is able to soak in for some time, it is possible that darker designs show some white discolouration. These spots will disappear within 24h. The floor can feel more slippery when it becomes wet. Spots, marks and spillages should be wiped up as soon as possible. Never use wax or varnish coating. Never use maintenance products that contain wax or oil. Never use a steam mop.

BERRYALLOC MAINTENANCE PRODUCTS




Cleaner

A special active cleaner for use on new floors immediately after installation and for the routine cleaning of floors factory-cured with a polyurethane finish as well as vinyl treated with PU Protect. Excellent dirt-binding properties, even in the case of fatty deposits. Causes no damage to the floor surface, does not cause greying (development of grey filming) and leaves no residues on the floor.



PU Protect

Matte polish for the initial protection of newly-laid/thoroughly cleaned floors and subsequent routine cleaning. When dry, it forms an anti-slip matte finish. Ideal for domestic use.



GENERAL MAINTENANCE PRODUCTS

- Must be PH neutral
 - If acidic: it may react with the floor and cause discoloration or odour nuisance
 - If basic: it may cause discoloration
- No bleach or chlorinated compounds: it may cause discoloration
- No acetone: it may affect the protective layers
- Alcohol-based cleaners: ok to be used if compliant with the above guidelines

STAIN REMOVAL

1. Clean with a wet floor cloth and use a solution of BerryAlloc cleaning agent in water.
2. Do not leave any puddles of water on the floor (only moisten the floor).
3. Let the product work in for minimum 10 and maximum 15 minutes.
4. Clean with a brush in two different directions.
5. Finally clean with a wrung wet rag until the water is clean again.

Tip: when you are dealing with a particular difficult stain, graffiti wipes might offer a solution. First, let the stain dry out. Then, use the wipes to clean the surface. After the stain is removed, rinse the floor with water to avoid leaving a greasy residue on the surface. Be careful not to leave any puddles of water on the floor.